

A black and white photograph of a golf course. In the foreground, there is a concrete path leading to a landscaped area with rocks and tall grasses. In the background, there are several trees and a building with a large canopy.

52 Golf Rd, Oakleigh
South
Summerset

Stormwater Management Plan

REPORT REVISION: C

Report Date: December 2022

Commercial in Confidence

This document is commercial-in-confidence. The recipient of this document agrees to hold all information presented within as confidential and agree not to use or disclose or allow to use or disclosure of the said information to unauthorized parties, directly or indirectly, irrespective of the acceptance or rejection of the presentation or at any time before, during or after an agreement has been reached, without prior written consent.

This report is prepared by Colliers | Engineering & Design for exclusive use by its client only. No responsibility is accepted for the use of or reliance upon this report in whole or in part by any third party.

Limitations

The sole purpose of this report and the associated services performed by Colliers | Engineering & Design is to display information in accordance with the scope of services set out in the contract/quotation between Colliers | Engineering & Design and its client. The scope of works and services were defined by the requests of the client, by the time and budgetary constraints imposed by the client, and by the availability of access to site/s and information.

This report is prepared with information supplied by the client and possibly others which is presumed to be accurate and complete. No responsibility is accepted for information that is withheld, incorrect or that is inaccurate, nor for changes to the conditions over the passage of time or from latent circumstance or conditions. No warranty or guarantee is made in relation to the data, findings and conclusions expressed in this report.

This report has been compiled at the level of detail specified in the report and no responsibility is accepted for interpretations made at more detailed levels than so indicated.

Report Contact:

Name: James Barker
 Position: Manager – Water & Environment
 Phone: (03) 9562 7424

Document Control

REPORT REVISION

Version	Date	Details	Prepared	Checked	Approved	Signed
A	Dec 2022	Issued for Discussion	J. Barker	N. Matamala	J. Barker	J. Barker
B	Dec 2022	Issued for Discussion	J. Barker	N. Matamala	J. Barker	J. Barker
C	Dec 2022	Issued for Approval	J. Barker	N. Matamala	J. Barker	J. Barker

Table of Contents

1. OVERVIEW	1
2. EXISTING SITE	1
3. PROPOSED DEVELOPMENT	1
4. FLOODING	1
5. STORMWATER MANAGEMENT	2
6. STORMWATER QUALITY TREATMENT	2
7. ON-SITE DETENTION.....	3
8. FLOOD MITIGATION	3
9. SUMMARY	5
APPENDICES	6

List of Tables

Table 1. Post-Developed Catchment Break-Up	2
Table 2. On-Site Detention Parameters	3

List of Figures

Figure 1. The Site.....	1
Figure 2. Proposed Development Plan.....	1
Figure 3. Existing Overland Flow Path - Previous SMP (FMG).....	2
Figure 4. MUSIC Modelling.....	3
Figure 5. SPEL Stormsacks (left) and SPEL Hydrosystem (right).....	3
Figure 6. SPEL Storm Chamber	3
Figure 7. Hydrological Analysis.....	3
Figure 8. Critical Duration & Temporal Pattern Hydrographs	4
Figure 9. Existing Conditions 1% AEP Flood Depths	4
Figure 10. Mitigated Conditions 1% AEP Flood Depths	4
Figure 11. Existing Vs Developed Case Flood Afflux	4
Figure 12. SWMS Concept.....	5

Appendices

Appendix A	Figures
Appendix B	Calculations

1. Overview

Colliers Engineering & Design have been engaged by Summerset to prepare a Stormwater Management Plan (SMP) for the Site, located at 52 Golf Rd, Oakleigh South.

The plan outlines any stormwater quantity and quality measures required within the Site to comply with Council requirements.

The plan builds upon the previously accepted SMP prepared by the previous landowner with minor adjustments to reflect the proposed new land-use of an aged care facility and retirement village.

2. Existing Site

The Site is located in Oakleigh South, south-west of the Huntingdale Golf Club and north-east of the intersection between Centre Rd and Warrigal Rd, it has an area of 1.83 hectares (ha).

In existing conditions, the Site is substantially bare and is considered highly permeable. The Site falls towards the north-west corner. Natural topography data indicates approximately 2 m of fall across the Site to the north-west, from 58.2 m AHD at the south-east corner to 56.2 m AHD at the north-east corner, see Figure 1.



Figure 1. The Site

3. Proposed Development

Based on the current draft plan, the Site will be developed into a retirement village and will incorporate villas, an independent living apartment complex, and an aged care facility, see Figure 2.



Figure 2. Proposed Development Plan

This proposed development will increase the imperviousness of the Site resulting in higher (site derived) peak flow rates and stormwater pollutant loads.

4. Flooding

The site is not subject to any Special Building Overlays or Land Subject to Inundation, which indicates that the site should not be prone to stormwater overflow that would result in a 1% AEP storm event. Notwithstanding, Council engineers have indicated that the development site is subject to overland flows during storm events.

The runoff comes from the intersection of Bakers Road and Beryl Avenue and travels in a north/west direction where it has been captured in the existing channel along the northern boundary to avoid discharging into existing dwellings at Barholme Court. The existing channel along the northern boundary was constructed to divert the runoff away from these court bowl properties.



Figure 3. Existing Overland Flow Path - Previous SMP (FMG)

5. Stormwater Management

The stormwater management for the development will be based on water sensitive urban design (WSUD) principles and will be consistent with Urban Stormwater Best Practice Environmental Management Guidelines while also incorporating sustainable design features to deliver lower living costs for future residents of the proposed development. The following key items will be considered:

- Adequate drainage to ensure a free draining development.
- Pavement, road, and drainage levels are designed to ensure surrounding properties are not adversely affected.
- The discharge volumes of the development are stored to pre-developed levels.
- The pollutant discharge from the Site is minimized to meet Best Practices, ensuring the protection of downstream receiving waterways and environments.
- Rainwater Harvesting, promoting self-sufficiency and cost-effective water practices.
- All flows, including up to the 1% AEP to be conveyed below ground, ensuring a reduction in any slipping or tripping hazards to the vulnerable residents of the retirement village by the removal of kerbs from the road's design.
- All flows to discharge via the Legal Point of Discharge (LPD) to Council satisfaction.

The proposed development has a total catchment area of 1.83ha.

Table 1. Post-Developed Catchment Break-Up

Land Use	Fraction Impervious	Area (ha)
Road/Pavement	1.00	0.435
Grass/Open Space	0.05	0.614
Buildings [Villas]	1.00	0.449
Buildings [ALA/RAC]	1.00	0.328
Total	0.68	1.826

6. Stormwater Quality Treatment

The strategy for on-site stormwater quality treatment to achieve Best Practice Environmental Guidelines has been achieved by an integrated approach with a combination of rainwater harvesting and stormwater quality improvement devices.

Best Practice Environmental Management Guidelines (BPEMG), which are:

- 45% reduction in Total Nitrogen (TN)
- 45% reduction in Total Phosphorus (TP)
- 80% reduction in Total Suspended Solids (TSS)
- 70% reduction in Litter (GP)

Rainwater harvesting is utilised on the apartment complex and aged care facility to address ESD requirements. As all flows are directed underground, proprietary treatment is the only option to achieve the remaining water quality objectives. Surface flows receive primary treatment (TSS & GP) at source via decentralised SPEL Stormsacks in each roadside pit. Tertiary treatment (TN & TP) is achieved via a SPEL Hydrosystem end of line filter prior to discharge to the LPD.

MUSIC modelling of the proposed treatment train confirms that Best Practice objectives have been achieved with sufficient conservatism.



Figure 4. MUSIC Modelling

Stormwater quality improvement devices are to be owned and maintained by the body corporate.




Figure 5. SPEL Stormsacks (left) and SPEL Hydrosystem (right)

7. On-Site Detention

An on-site detention (OSD) system will be constructed to protect the downstream receiving environment from increased (developed) flows. The OSD system has been sized using Boyd's Method where the 1% AEP developed flows developed within the Site were restricted to that of pre-developed conditions.

Storage is achieved via an underground detention tank (SPEL Storm Chamber). Table 2 highlights the storage requirements to detain flows to pre-developed conditions.

Table 2. On-Site Detention Parameters

Restricted Outflows	0.19 m ³ /s
Peak Inflows	0.65 m ³ /s
Storage Volume Required	250 m ³

The outfall for the OSD system will discharge into the Council drainage network. As the OSD system is being proposed to be below ground, the location of the asset will be within the village road reserve close to the legal point of discharge at the north-west corner.




Figure 6. SPEL Storm Chamber

8. Flood Mitigation

The Site is subject to flooding from Bakers Rd and drainage network to the south with overland flows discharging through the Site and into existing residences within Barholm Ct and Golf Rd. The previously accepted proposal by the former landholder to mitigate this was achieved via directing these overland flows safely through the site via the internal road network.

As the new land-use is intended to contain aged care facilities for vulnerable residents, no tripping hazards (such as kerbs) are permitted within the site. As such, external flooding is to be mitigated by directing overland flows safely underground through the Site. Two-dimension flood modelling (TuFLOW) was undertaken to confirm this approach.

Hydrologic modelling (RORB) to ARR19 methodology was undertaken to determine the critical 1% AEP storm event flows within the area.




Figure 7. Hydrological Analysis

The 1% AEP existing conditions was run to determine the critical duration (20-min) and temporal pattern (27TPat) at

the Site Inlet at the eastern boundary of the Site. At this critical duration and temporal pattern, hydrographs have been developed, by extracting flows from the print nodes in the RORB model located at Beryl Avenue, Bakers Road, Joyce Avenue, and Cameron Avenue close to the Site, refer Figure 8.




Figure 8. Critical Duration & Temporal Pattern Hydrographs

These hydrographs were used in the hydraulic analysis to inject flows into the TuFLOW model in order to determine the extent of flooding at the Site's outlet along Golf Rd and inform on the quantity of external flows entering the Site, while incorporating the surrounding drainage network.



Figure 9. Existing Conditions 1% AEP Flood Depths

Flood mitigation scenario modelling was undertaken utilising an iterative approach with the goal of achieving no overland flows within the site and no increase in flood risk to surrounding properties (both up-and-downstream) during the 1% AEP rainfall event as a result of the development.

Floodwaters from Bakers Rd are to be captured via a grated pit within the Site and directed towards the LPD via underground drainage.



Figure 10. Mitigated Conditions 1% AEP Flood Depths

An Afflux plot (flood depth comparison) between existing and developed conditions is highlighted below. There are significant reductions in flooding within the site and within the existing dwellings to the north (pink).




Figure 11. Existing Vs Developed Case Flood Afflux

A summary of the flood mitigation proposal includes:

- Residences of Golf Rd and Barholme Ct are no longer inundated in major storm events
- Reduced flood levels at the northern end of Bakers Rd
- A minor increase in flood depths down Golf Rd due to the diversion of flows preventing the flooding of households whilst maintaining adequate freeboard to lots adjacent to Golf Rd.

The proposed mitigation design is successful in the conveyance of overland flows through the development in a controlled manner with the major upshot of entirely removing the pre-existing flood risk to eight properties directly north of the subject site.

9. Summary

The proposed SMP achieves all Council requirements for stormwater management for the site. Including provision for flood mitigation, on-site detention and water quality treatment, while also incorporating rainwater harvesting.

Flood mitigation measures proposed not only provide flood protection via redirecting of flood waters underground for vulnerable residents within the site, but also improves existing flooding for surrounding properties.

On-site detention has been sized to restrict developed conditions flows to that of existing conditions via underground tank storage.

Water quality objectives have been achieved via a combination of rainwater harvesting, decentralised primary treatment within roadside pits and end of line tertiary treatment via a proprietary filter.

On-site drainage assets are to be owned and maintained by the retirement village operator.




Figure 12. SWMS Concept

Appendices

Appendix A Figures

Legend










- Site
- LIDAR Contours (200mm)




				On behalf of	Project Title	Golf Rd (52) Oakleigh South	Date	29/11/2022
					Project Number	#22-0331	Drawn By	N.Matamala
					Drawing Title	Site Overview	Checked By	O.Taha

Disclaimer: All GIS information is indicative and should be confirmed

Legend

-  Site Boundary
 -  PARCEL
 -  Contributing Catchment
 -  LIDAR Contours (200mm)
 - Channels
 -  1
 -  2
 -  3
 -  4
- cep01_melbourne-lidar2018_dem1m_gda2020mga55
Band 1
-  54.720000
 -  57.855000
 -  60.990000
 -  64.125000
 -  67.260000



On behalf of



1:2000

Project Title Golf Rd (52) Oakleigh South

Date 10/10/2022

Project Number #22-0331










Drawn By N.Matamala

Drawing Title Hydrological Analysis

Checked By O.Thaha




Legend

-  Site Boundary
- Flood Depths (m)
Band 1
-  0.00 - 0.03m
-  0.03 - 0.05m
-  0.05 - 0.10m
-  0.10 - 0.25m
-  0.25 - 0.50m
-  0.50 - 1.00m
-  1.00 - 1.50m
-  Greater than 1.50m












On behalf of



Project Title	Golf Rd (52) Oakleigh South	Date	01/12/2022
Project Number	#22-0331	Drawn By	N. Matamala
Drawing Title	1% AEP Flood Depths - Existing	Checked By	J. Barker




Legend

-  Site Boundary
- Golf Rd_pr02_100y_20mtp27_v1_d_Max Band 1
-  0.00 - 0.03m
-  0.03 - 0.05m
-  0.05 - 0.10m
-  0.10 - 0.25m
-  0.25 - 0.50m
-  0.50 - 1.00m
-  1.00 - 1.50m
-  Greater than 1.50m



On behalf of

















Project Title	Golf Rd (52) Oakleigh South	Date	01/12/2022
Project Number	#22-0331	Drawn By	N. Matamala
Drawing Title	1% AEP Flood Depths - Developed	Checked By	J. Barker





Legend

- Site**
-  Site Boundary
 -  Was Wet Now Dry
 -  Was Dry Now Wet
- Afflux**
-  <-1.0m
 -  -1.0 - -0.50m
 -  -0.50 - -0.25m
 -  -0.25 - -0.15m
 -  -0.15 - -0.1m
 -  -0.1 - -0.05m
 -  -0.05 - -0.03m
 -  0.03 - 0.05m
 -  0.05- 0.15m
 -  0.15 - 0.25m
 -  > 0.50m



On behalf of

0 15 30 45 60 75 m

1:1200

Project Title Golf Rd (52) Oakleigh South


Date 12/10/2022

Project Number #22-0331

Drawn By C.Cosgriff

Drawing Title Afflux - Wet Dry Analysis

Checked By O.Thaha




Legend


- Site
 - Site Boundary
- SWMS
 - Underground Drainage Flows
 - SPEL Hydrosystem
 - SPEL Stormsacks (Indicative)
 - Underground Detention Basin
 - 100yr External Pipe
- Golf_Rd_pr02_100y_20mtp27_v1_d_Max Band 1
 - 0.00 - 0.03m
 - 0.03 - 0.05m
 - 0.05 - 0.10m
 - 0.10 - 0.25m
 - 0.25 - 0.50m
 - 0.50 - 1.00m
 - 1.00 - 1.50m
 - Greater than 1.50m



On behalf of



Project Title	Golf Rd (52) Oakleigh South	Date	30/11/2022
Project Number	#22-0331	Drawn By	N.Matamala
Drawing Title	SWMS Concept	Checked By	O.Thaha



Appendix B


Calculations



Project Name: Golf Road (52) Oakleigh South
Project No.: 22-0331
Author: Nicholas Matamala
Date: 29/11/2022

Description: Detention Tank

Definitions



Boyd's Equation:
$$S_{max} = V_i \left(1 - \frac{Q_o}{Q_p} \right)$$

Where:
 S_{max} = Maximum Volume of Temporary Storage (m³)
 V_i = Volume of Inflow Flood (m³)
 Q_p = Peak discharge of inflow hydrograph (m³/s)
 Q_o = Peak discharge of outflow hydrograph (m³/s)

Input

Pre-Developed Catchment Modelling						
AEP	Area Ha	Cy	Tc min	I mm/hr	Σ Ae Ha	Q m ³ /s
63.20%	1.826	0.185	19.13	33.30	0.338	0.03
50%	1.826	0.197	18.06	38.45	0.359	0.04
20%	1.826	0.220	15.42	57.02	0.401	0.06
10%	1.826	0.231	14.05	71.99	0.423	0.08
5%	1.826	0.243	12.94	88.42	0.444	0.11
2%	1.826	0.266	11.70	113.66	0.486	0.15
1%	1.826	0.278	10.91	135.42	0.507	0.19

Post-Developed Catchment Modelling						
AEP	Area Ha	Cy	Tc min	I mm/hr	Σ Ae Ha	Q m ³ /s
63.20%	1.826	0.530	7.25	54.41	0.968	0.15
50%	1.826	0.563	7.25	60.71	1.029	0.17
20%	1.826	0.630	7.25	82.08	1.150	0.26
10%	1.826	0.663	7.25	98.11	1.211	0.33
5%	1.826	0.696	7.25	115.01	1.271	0.41
2%	1.826	0.762	7.25	139.51	1.392	0.54
1%	1.826	0.796	7.25	159.94	1.453	0.65

Storage Release	AEP	1%
	AEP	1%

Discharge 0.19 m³/s

Storage Calculation



Volume Required 250 m³ Okay

Dur (mins)	I (mm/hr)	C	A	Ae	I _p (m ³ /s)	Q _p (m ³ /s)	V _i (m ³)	S _{max} (m ³)	Check
5.00	180.02	0.80	1.826	1.453	0.726	0.19	217.9	160.7	More Storage
6.00	170.48	0.796	1.826	1.453	0.688	0.19	247.7	179.0	More Storage
7.00	161.94	0.796	1.826	1.453	0.653	0.19	274.5	194.3	More Storage
8.00	154.22	0.796	1.826	1.453	0.622	0.19	298.7	207.1	More Storage
9.00	147.20	0.796	1.826	1.453	0.594	0.19	320.7	217.7	More Storage
10.00	140.79	0.796	1.826	1.453	0.568	0.19	340.9	226.4	More Storage
11.00	134.92	0.796	1.826	1.453	0.544	0.19	359.3	233.4	More Storage
12.00	129.53	0.796	1.826	1.453	0.523	0.19	376.3	239.0	More Storage
13.00	124.57	0.796	1.826	1.453	0.503	0.19	392.1	243.3	More Storage
14.00	119.97	0.796	1.826	1.453	0.484	0.19	406.7	246.4	More Storage
15.00	115.72	0.796	1.826	1.453	0.467	0.19	420.3	248.6	More Storage
16.00	111.77	0.796	1.826	1.453	0.451	0.19	433.0	249.8	More Storage
17.00	108.09	0.796	1.826	1.453	0.436	0.19	444.9	250.3	Okay



Treatment Train Effectiveness - LPoD

	Sources	Residual Load	% Reduction
Flow (ML/yr)	7.93	6.52	17.8
Total Suspended Solids (kg/yr)	707	134	81.1
Total Phosphorus (kg/yr)	1.96	0.755	61.4
Total Nitrogen (kg/yr)	19.5	8.47	56.6
Gross Pollutants (kg/yr)	261	0	100





At Colliers,
we are
enterprising.

We maximise the potential of property to accelerate the success of our clients and our people.

Our expert advice to property occupiers, owners and investors leads the industry into the future. We invest in relationships to create enduring value. What sets us apart is not what we do, but how we do it. Our people are passionate, take personal responsibility and always do what's right for our clients, people and communities. We attract and develop industry leaders, empowering them to think and act differently to drive exceptional results. What's more, our global reach maximizes the potential of property, wherever our clients do business.

colliers.com.au

